

Sukup®

Spredway®

G R A I N S P R E A D E R S



The features you want:

- The most reliable grain spreader you can buy.
- Pre-spread disc and inner ring help provide even spreading. The optional pre-spread funnel further enhances even spreading.
- Totally-enclosed, continuous-duty motors mounted outside spreader cone for optimum performance.

In a size you need:

- **Standard Spredway** - 3000 bph, ½ hp motor, fits up to 33' dia. bins.
- **High-Capacity Spredway** - 3000 - 5000 bph, ¾ hp motor, fits up to 48' bins.
- **Super High-Capacity Spredway** - 5000 - 7000 bph, 1 ½ hp motor, fits up to 60' dia. bins.

The Best-Selling Grain Spreader - Spredway

Outstanding features have made the reliable Sukup Spredway #1!

Grain Flow is Unobstructed

- There are no motors or gear boxes inside the spreader funnel to hamper grain flow.
- Mounting the motor outside of the spreader cone prevents warm grain from overheating the motor.


Easily Adjustable Pan

- The angle of the Spredway spreader pan can be easily adjusted from the top to control the grain distribution pattern.
- The handle is easily accessible, unlike other spreaders which must be adjusted from below the unit or with a special tool.
- Adjusting the pan matches the grain spread distance to different bin diameters.
- A Split Spreader Pan (standard) divides the grain discharge resulting in a more evenly balanced flow, which makes the spreader operate more smoothly.



Uniform Grain Flow

The pre-spread disc and ring, standard on all Spredways, combine to create a uniform flow of grain to the spread pan for even spreading.



Totally Enclosed, High-Horsepower Motor

All Sukup Spredways are equipped with heavy-duty, high-horsepower motors to ensure optimum performance. Horsepower ratings for the different models are listed in the chart below.

Rigid Mounting Brackets

- Special, two-piece design allows for vertical and horizontal adjustment to level the spreader.
- The rigid mount prevents spreader movement.
- Additional hanger brackets are available for mounting in bins that are not compatible with the rigid brackets.



Dependable

- The simple design of the Spredway includes a machined pulley to ensure that the drive belt remains in position under the heaviest grain flow conditions.
- No gearbox and a minimum of moving parts make Spredway the most dependable grain spreader you can buy.
- Permanently-lubricated bearings eliminate climbing the bin to grease bearings or oil gears.

Exclusive Pre-Spread Funnel

Most problems with uneven spreading occur when grain does not fall into the center of the grain spreader. The Sukup Pre-Spread Funnel is an optional accessory that directs grain to the center of the Spredway's pre-spread disc, creating even and uniform spreading action.



Spredway® Specifications

Spredway Model	Capacity - bu/hr	Motor Size	Pre-Spread disc dia.	Spreader Pan Style	Motor Pulley Dia.	Cone	Bin Dia.
Standard	up to 3000	1/2 hp	3 1/2"	Split	1 3/4"	19" x 12"	18' - 33'
High Cap.	3000 - 5000	3/4 hp	3 1/2"	Split	2 1/4"	19" x 12"	24' - 48'
Super High Cap.*	5000 - 7000	1 1/2 hp	8"	Split	2 1/4"	19" x 13"	36' - 60'

*Super High Cap Spredway is painted, not galvanized. Specifications are subject to change.



Sukup Manufacturing Co. ■ www.sukup.com

1555 255th St. ■ Box 677 ■ Sheffield, IA, USA 50475-0677 ■ Phone: 641-892-4222

© Fax: 641-892-4629 ■ Email: info@sukup.com

Distribution Centers Located In:

Arcola, IL 61910
980 E. State Rte.
217-268-3026

Aurora, NE 68818
1705 Hwy. 34 E.
402-694-5922

Defiance, OH 43512
7724 Rte. 66 N.
419-784-9871

Jonesboro, AR 72403
5917 E. Johnson Ave.
870-932-7547

Cameron, MO 64429
7426 NE 352nd St.

Watertown, SD 57201
2701 Piper Ave.
605-882-6697